






Republic of the Philippines
 PROVINCE OF BUKIDNON
 Municipality of Manolo Fortich



**ACCESSIBILITY SURVEY CHECKLIST
 BASED ON BATAS PAMBANSA BILANG 344 (ACCESSIBILITY LAW)**

Name of Building Establishment : _____
 Address : _____
 Owner : _____
 No. Of Floors / Storeys: : _____
 Instructions: : Put check mark (✓) if accessible facilities/ features are compliant with the minimum requirements and cross mark (✗) if missing/non-complaint

| | ACCESSIBILITY FEATURES | ACTUAL DIMENSIONS/ DESCRIPTION/REMARKS |
|---|--|---|
| <input type="checkbox"/> Accessible Ramps  Fig. A.3.1 | <input type="checkbox"/> Located at / near main entrance | |
| | <input type="checkbox"/> Gradient (1:12 maximum) | |
| | <input type="checkbox"/> Equal or flatter than 1:12 | |
| | <input type="checkbox"/> Steeper than 1:12 | |
| | <input type="checkbox"/> Handrails on both sides with the following: | |
| | <input type="checkbox"/> Two (2) sets: 1- 0.90m high and 1- 0.70m high measured from ramp floor to Top of handrail | |
| | <input type="checkbox"/> With 0.30m extensions at the start and end of handrails | |
| | <input type="checkbox"/> Handrail Diameter between 30mm - 50mm | |
| | <input type="checkbox"/> Clearance of 50mm if wall mounted | |
| | <input type="checkbox"/> Maximum length is 6.00m | |
| | <input type="checkbox"/> Provision of 1.50m (minimum) landing between every 6.00m length of ramp | |
| | <input type="checkbox"/> Clear width of ramp is 1.20m | |
| | <input type="checkbox"/> Curbs on both sides, 100mm high | |
| | <input type="checkbox"/> Non skid flooring / finish | |
| | <input type="checkbox"/> Level area (1.80m min.) provided at the start and end of ramp/s | |
| <input type="checkbox"/> With signage using the international symbol of access (white graphics with United Nations blue background) | | |

| | ACCESSIBILITY FEATURES | ACTUAL DIMENSIONS/ DESCRIPTION/ REMARKS |
|--|---|--|
| <div data-bbox="224 247 344 279" data-label="Section-Header"> <p><input type="checkbox"/> Parking</p> </div>  <p data-bbox="178 472 397 493">Fig. A.4.2: ACCESSIBLE PARKING SLOT (3D VIEW)</p> | <input type="checkbox"/> Located nearest to accessible building entrance | |
| | <input type="checkbox"/> Minimum Dimension: 3.70m (width) x 5.00m (length) | |
| | <input type="checkbox"/> Accessible walkway from parking with 1.20m clear width | |
| | <input type="checkbox"/> Provision of curb cut-outs / dropped curbs if adjacent walkways are higher than parking level | |
| | <input type="checkbox"/> With signage using the International Symbol of Access (white graphics with United Nations blue Background) | |
| <div data-bbox="224 667 373 724" data-label="Section-Header"> <p><input type="checkbox"/> Washroom and Toilet</p> </div>  <p data-bbox="154 913 414 934">Fig. C.6.1: PLAN OF ACCESSIBLE TOILET FOR PERSONS WITH DISABILITIES</p> | <input type="checkbox"/> Clear dimension of Toilet Cubicle 1.70m x 1.80m | |
| | <input type="checkbox"/> Water closet 0.40m measured from the center of the toilet bowl to the face of adjacent wall | |
| | <input type="checkbox"/> Permit easy passage of wheelchair (1.50m turning space) | |
| | <input type="checkbox"/> Door swings out | |
| | <input type="checkbox"/> Clear opening of door is 0.80m | |
| | <input type="checkbox"/> Accessible Toilet accessories: | |
| | <input type="checkbox"/> One (1) fixed grab bar mounted at 0.80m (measured from FFL to top of grab bar) | |
| | <input type="checkbox"/> one (1) movable grab bar (outrigger) | |
| | <input type="checkbox"/> Tilted mirror <input type="checkbox"/> Lever - type faucet | |
| | <input type="checkbox"/> Lavatory is 0.80m high w/ knee space of between 0.60m - 0.70m underneath | |
| | <input type="checkbox"/> Non skid flooring | |
| | <input type="checkbox"/> Signage: Mounted 1.50m O.C. from finish floor line using International symbol of Access (ISA) | |
| | <input type="checkbox"/> ISA in shape of equilateral triangle for men | |
| <input type="checkbox"/> ISA in the shape of a circle for women | | |

| ACCESSIBILITY FEATURES | | ACTUAL DIMENSIONS/ DESCRIPTION/ REMARKS |
|---|--|--|
| <input type="checkbox"/> Entrances, Doors Corridors | <input type="checkbox"/> Entrance vestibules / porches with level area of at least 1.80m (depth) and 1.50m (width) Minimum | |
| | <input type="checkbox"/> Clear door opening of 0.90m (minimum) | |
| | <input type="checkbox"/> Door uses lever- type Locksets | |
| | <input type="checkbox"/> Corridors with minimum clear width of 1.20m | |
| | <input type="checkbox"/> Non - skid flooring / finishes | |
| | <input type="checkbox"/> With Directional signages | |

OTHER COMMENTS / REMARKS:

Members of Accessibility Survey Team

(Signature Over Printed Name)

(Signature Over Printed Name)

(Signature Over Printed Name)

(Signature Over Printed Name)

(Signature Over Printed Name)

(Signature Over Printed Name)